



Safety Data Sheet

REMA TIP TOP

Product #: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: UT-R20 Hardener

Chemical Family: Halogenated Hydrocarbons & Di-isocyanates Solution

Product Use: Adhesive/Cement Hardener

Restrictions on Use: Use as directed by manufacturer

Manufacturer: Rema Tip Top - North America
119 Rockland Ave.
Northvale, NJ 07647
Phone: 201 256-8200

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. HAZARD IDENTIFICATION

GHS Classifications

Health Hazards

Skin Irritation, Category 2

Eye Irritation, Category 2A

Respiratory Sensitization, Category 1A

Skin Sensitization, Category 1A

Carcinogenicity, Category 2

Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Respiratory Tract [Inhalation]

Specific Target Organ Systemic Toxicity, Repeated Exposure, Category 2, Central Nervous System, Blood, Heart, Kidney, Liver, Pancreas, Respiratory Tract [Inhalation, Skin absorption, Ingestion]

GHS-Labeling

Pictograms:



Signal Word: Danger!

Hazard Statements

Page 1 of 11

SDS ID: RTT-IND-012



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

H315: Causes skin irritation
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335: May cause respiratory irritation
H351: Suspected of causing cancer
H373: May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention:

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P260: Do not breathe vapors.
P264: Wash skin and exposed areas thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P281: Use personal protective equipment as required.
P285: In case of inadequate ventilation, wear respiratory protection.

Response:

P301 + P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P341: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313: IF exposed or concerned: Get medical advice/attention.
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313: If eye irritation persists: Get medical advice/attention.
P342 + P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362: Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up

Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical characterization

Halogenated Hydrocarbons & Di-isocyanates Solution

Component*	CAS #	% By Wt.
Dichloromethane (Methylene chloride)	75-09-2	60 - 75
Diphenylmethane di-isocyanate, isomers and homologues	9016-87-9	10 - 30
Dibutyltin Dilaurate	77-58-7	0.1 - < 1

*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

4. FIRST AID MEASURES

Inhalation

Symptoms & Effects: Nausea, nose and throat irritation, headache, respiratory tract irritation, breathing difficulties, allergy or asthma symptoms

Measures: Immediately remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, begin artificial respiration. If breathing is difficult, administer oxygen. Seek immediate medical attention.

Skin Contact

Symptoms & Effects: Skin irritation, redness, allergic reactions, skin drying

Measures: Wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes while washing. Wash contaminated clothing before reuse. If skin irritation persists, seek medical attention.

Eye Contact

Symptoms & Effects: Eye irritation, stinging, tearing, redness, eye swelling

Measures: Immediately rinse eyes with water for at least 15 minutes. Remove contact lenses after the initial few minutes and if easy to do so and resume rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while rinsing. Seek immediate medical attention.

Ingestion

Symptoms & Effects: Stomach or intestinal irritation, nausea, vomiting, diarrhea, respiratory tract irritation

Measures: Seek immediate medical attention. Do NOT induce vomiting unless directed to do so by a physician or medical personnel. If the victim is drowsy or unconscious, do not give anything by mouth. Do not give milk. Place individual on their left side and place their head down. Do not leave victim unattended.



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Alcohol-resistant foam, Carbon dioxide, Dry chemical, Water spray

Unsuitable Extinguishing Media: Water stream/jet

Hazardous Combustion Products: Hydrogen cyanide (HCN), Hydrogen chloride gas, Chlorine, Phosgene (trace amounts), Nitrogen oxides (NO_x), Carbon monoxide, Carbon dioxide

Protective Equipment for Fire-Fighters: Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Precautions for Fire-Fighters: Water stream may be ineffective for extinguishment unless used under favorable conditions. This product is volatile and readily gives off flammable vapors which may travel along the ground or be moved by ventilation. Do not allow run-off from firefighting to enter drains or water courses. Use water spray to cool fully closed containers. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Recommended to wear NIOSH approved respiratory apparatus, chemical splash goggles & resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

Personal Precautions: Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

Environmental Precautions: Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by constructing a dike or using oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Methods & Materials for Clean-Up: Immediately evacuate the spilled area and provide maximum ventilation. Only personnel equipped with proper respiratory, eye, and skin protection should be permitted in the area. Contain spilled material with inert, non-combustible absorbent materials such as sand, earth, diatomaceous earth, or vermiculite. Transfer to a suitable container for disposal according to proper federal, state, and local regulations. Notify the proper response units and agencies for any uncontained releases or spills.



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

7. HANDLING AND STORAGE

Handling: Avoid breathing vapors or mists of this product. Avoid eye and skin contact with this material. Skin and eye PPE should be worn at all times when handling this product. When adequate ventilation is not provided, respiratory PPE should also be used. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Do not eat, drink or smoke when using this product.

Storage: Store in a cool, dry, ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed and store locked up. Keep away from food, drink, and animal foodstuffs.

Incompatible Materials: Water, Alkaline metals, Amines, Alcohols, Strong acids, Strong bases, Strong oxidizing agents, Aluminum, Magnesium, Vinyl compounds

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits :

Exposure limits have not been established for this product.

Dichloromethane CAS # 75-09-2

OSHA	Permissible Exposure Limit (PEL)	25 ppm/125 ppm (STEL)
ACGIH	Time Weighted Average (TWA)	50 ppm

Diphenylmethane di-isocyanate, isomers and homologues

CAS # 9016-87-9

OSHA	Permissible Exposure Limit (STEL)	0.02 ppm (0.2 mg/m ³)
ACGIH	Time Weighted Average (TWA)	0.005 ppm (0.05 mg/m ³)
NIOSH	Recommended Exposure Limit (REL)	0.003 ppm (0.05 mg/m ³)

Tin, organic, as Sn

CAS # NA

OSHA	Permissible Exposure Limit (TWA)	0.1 ppm
ACGIH	Time Weighted Average (TWA/STEL)	0.1/0.2 ppm
NIOSH	Recommended Exposure Limit (REL)	0.01 ppm

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. Provide readily accessible eye wash stations and safety showers.

Occupational Exposure Controls: Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

Protective and Hygiene measures: Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

Eye Protection: Recommended to wear tight fitting, chemical splash goggles when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

Hand Protection: Recommended to wear suitable resistant gloves and discard of gloves that show tears, pinholes, or signs of wear. Suitable gloves will be based on product use and the period of use, and may include neoprene, butyl-rubber, nitrile rubber, etc.

Skin Protection: Recommended to wear long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Brown Liquid

Odor: Sweet

Odor Threshold: 200 – 300 ppm

pH: No data available

Melting/Freezing point: No data available

Boiling Point/ Range: 104°F (40°C)

Flash point (Tag closed cup): > 200°F (> 93°C)

Evaporation rate: No data available

Flammability: Lower Limit: 13.0% (V) **Upper Limit:** 22.0% (V)

Vapor pressure: 355 mmHg @ 68°F (20°C)

Relative vapor density: > 1 (Air = 1)

Density: 1.32 g/cm³ (11.0 lbs/gal) @ 68°F (20°C)

Solubility in water: Insoluble; Reacts with water

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Ignition temperature: No data available

Decomposition temperature: No data available



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

Viscosity (dynamic): No data available

10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Product will not undergo hazardous polymerization or other hazardous reactions if storage and use directions are followed.

Conditions to Avoid: Exposure to water, Elevated temperatures, Incompatible materials (see below)

Incompatible Materials: Water, Alkaline metals, Amines, Alcohols, Strong acids, Strong bases, Strong oxidizing agents, Aluminum, Magnesium, Vinyl compounds

Hazardous decomposition products: Hydrogen cyanide (HCN), Hydrogen chloride gas, Chlorine, Phosgene (trace amounts), Nitrogen oxides (NO_x), Carbon monoxide, Carbon dioxide

11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation, Skin contact, Eye contact, Ingestion

Symptoms Related to Physical, Chemical and Toxicological Characteristics: Nausea, nose and throat irritation, headache, respiratory tract irritation, breathing difficulties, allergy or asthma symptoms, skin irritation, skin redness, allergic reactions, skin drying, eye irritation, stinging, tearing, eye redness, eye swelling, stomach or intestinal irritation, vomiting, diarrhea

Delayed and Immediate Effects & Chronic Effects from Exposure: This substance may result in respiratory irritation, asthma symptoms or breathing difficulties on inhalation. This substance may lead to allergic skin reactions or skin breakouts. With repeated exposure, the substance may have toxic effects on the central nervous system, blood, heart, kidneys, liver, pancreas, and respiratory tract. This substance is a suspected carcinogen as outlined by OSHA, IARC, and the NTP (see below).

Measures of Toxicity:

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: LD₅₀ Rat: > 1,700 mg/kg

Acute Dermal Toxicity: No sufficient data available

Acute Inhalation Toxicity: LC₅₀ Rat: > 39 mg/l

Dichloromethane

Acute Oral Toxicity

Acute Inhalation Toxicity

CAS # 75-09-2

LD₅₀ Rat: 1,600 mg/kg

LC₅₀ Rat: 52,000 mg/m³



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

Isocyanic Acid, Polymethylenepolyphenylene

Ester

Acute Inhalation Toxicity

CAS # 9016-87-9

LC₅₀ Rat: 0.49 mg/l

Dibutyltin Dilaurate

Acute Oral Toxicity

CAS # 77-58-7

LD₅₀ Rat: 175 mg/kg

Acute Dermal Toxicity

LD₅₀ Rabbit: > 2,000 mg/kg

Acute Inhalation Toxicity

LC₅₀ Mouse: 0.15 mg/l

Carcinogen Claims:

OSHA: **Yes**; International Agency for Research on Cancer (IARC): **Yes; 2B [Possibly Carcinogenic to Humans]**, National Toxicology Program (NTP) Report on Carcinogens: **Yes; II [Reasonably Carcinogenic]**

12. ECOLOGICAL INFORMATION

Eco-toxicity: This substance is not expected to be harmful to aquatic organisms; however it is still strongly advised that this substance does not enter the environment.

Dichloromethane CAS # 75-09-2

Toxicity to Fish LC₅₀ – 193 mg/l (Fathead Minnow; 96 h)

Toxicity to Daphnia EC₅₀ – 1,682 mg/l (Water Flea; 48 h)

Persistence & Degradability: No data available

Bio-accumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No data available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.

Contaminated packaging should be emptied as far as possible before disposal.

RCRA Waste Numbers: Dichloromethane: U080

14. TRANSPORT INFORMATION

DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1593

PROPER SHIPPING NAME: Dichloromethane, mixture

TRANSPORTATION HAZARD CLASS: 6.1

PACKING GROUP: III

HAZARD LABEL: 6.1

Page 8 of 11

SDS ID: RTT-IND-012



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 6.1

UN NUMBER: UN1593

MARINE POLLUTANT: No

EmS: F-A, S-A

IMDG PACKING GROUP: III

HAZARD LABEL: 6.1

Description of the goods

DICHLOROMETHANE, mixture

IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 6.1

UN NUMBER: UN1593

HAZARD LABEL: 6.1

Description of the goods

Dichloromethane, mixture

15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

SARA Title III

Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

None Listed

Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Component	CAS #	Weight %	CERCLA RQ
Dichloromethane	75-09-2	60 – 75	1,000
Polymeric diphenylmethane diisocyanate	9016-87-9	10 – 20	--
MDI	101-68-8	5 – 10	5,000

OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements.

Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

CANADIAN REGULATIONS

WHMIS Classification: Same as OSHA GHS Classification



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

STATE REGULATIONS

California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer.

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List/Permissible Exposure List

California Toxic air contaminants

Connecticut Permissible Exposure Limits

Delaware List of Chemicals and RQs

Hawaii Permissible Exposure Limits

Idaho Toxic Air Pollutants

Illinois Toxic Air Contaminants List

Louisiana Toxic Air Pollutants

Maine Hazardous Air Pollutants

Maryland Toxic Air Pollutants for Existing Sources

Massachusetts Hazardous Substances List

Michigan Permissible Exposure Limits

Minnesota Hazardous Substances

Minnesota Permissible Exposure Limits

Nebraska Hazardous Air Pollutants

New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List

New York List of Hazardous Substances

Ohio Toxic Air Contaminants

Oklahoma Toxic Air Contaminants

North Carolina TAP Emissions Rates Requiring a Permit

Pennsylvania Hazardous Substances List

Rhode Island Toxic Air Contaminants

Tennessee Permissible Exposure Limits

Vermont Hazardous Air Contaminants/Permissible Exposure Limits

Washington Permissible Exposure Limits for Airborne Contaminants.

West Virginia Toxic Air Pollutant List

Wisconsin hazardous Air Contaminants

Note: Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.



Safety Data Sheet

REMA TIP TOP

Product #s: UTR20/20G, UTR20/40G

SDS #: RTT-IND-012

Rev. # 6

Rev. Date: 3/22/2017

16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
800-424-9300

FOR ANY OTHER INFORMATION:

REMA TIP TOP - NORTH AMERICA
119 Rockland Ave.
NORTHVALE, NJ 07647
201-256-8200

NOTICE: REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.